




NO	PAT. NO	NAME	MATL	QTY	TREAT	REMARK
1	M-631-PMD-R	3 PIN CONNECTOR	---	1	---	---
2	V-034PX-R	WIRE	UL2464 CORE 24AWG	3M	---	

NO	ELECTRICAL SPECIFICATIONS	
1	Rated current/voltage	3A-125V MAX. 5mA-5V MIN.
2	Operation limit voltage (AC.V.rms)	
3	Withstanding voltage (AC.V.rms) 1 minute	300
4	Insulation resistance (MΩ MIN.) at DC 500V	100



	NAME	DATE	ARTICLE NO:	REVISION:	TITLE:		
DRAWN	Halit Yılmaz						
CHECKED	Ahmet Altınışık		COMMENTS: This drawing is subject to technical modification without prior notice. Typographical and other errors do not justify any claims for damages. All dimensions should be verified using an actual produced part.				
ALTINKAYA ENCLOSURES FOR ELECTRONICS www.altinkaya.com.tr PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ALTINKAYA ENCLOSURES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ALTINKAYA ENCLOSURES IS PROHIBITED.					DİKKAT: BU RESİM VE ÜRÜN ÖNCEDEN HABER VERİLMEKSİZİN DEĞİŞTİRİLEBİLİR. RESİM ÇİZİLRKEN HATASIZ OLMASINA ÇALIŞILMASINA RAĞMEN RESİMDE HATALAR BULUNABİLİR. RESİMDEKİ HATALARDAN DOLAYI OLUŞABİLECEK ZARARLAR İÇİN ALTINKAYA HIÇ BİR SORUMLULUK KABUL ETMEZ. BÜTÜN ÖLÇÜLER KULLANILMADAN ÖNCE ÜRETİLMİŞ GERÇEK NUMUNEDEN KONTROL EDİLMELİDİR.		
			MATERIAL:		DWG NO. M-631-PMD3-R		
			WEIGHT:		SCALE:2:1	SHEET 1 OF 1	
					 A4		